

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.

1. REPORT DATE (DD-MM-YYYY)		2. REPORT TYPE Technical Papers		3. DATES COVERED (From - To)	
4. TITLE AND SUBTITLE <i>Please see attached</i>				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
				5d. PROJECT NUMBER 3058	
6. AUTHOR(S) <i>Please see attached</i>				5e. TASK NUMBER RF9A	
				5f. WORK UNIT NUMBER 346055	
				8. PERFORMING ORGANIZATION REPORT	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Air Force Research Laboratory (AFMC) AFRL/PRS 5 Pollux Drive Edwards AFB CA 93524-7048				10. SPONSOR/MONITOR'S ACRONYM(S)	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) Air Force Research Laboratory (AFMC) AFRL/PRS 5 Pollux Drive Edwards AFB CA 93524-7048				11. SPONSOR/MONITOR'S NUMBER(S) <i>Please see attached</i>	
12. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited.					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT					
20030121 099					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON
a. REPORT	b. ABSTRACT	c. THIS PAGE	A		Leilani Richardson
Unclassified	Unclassified	Unclassified			19b. TELEPHONE NUMBER (include area code) (661) 275-5015

TP-FY99-0060

9A

MEMORANDUM FOR PRS (Contractor Publication)

FROM: PROI (TI) (STINFO)

15 March 1999

SUBJECT: Authorization for Release of Technical Information, Control Number: **AFRL-PR-ED-TP-FY99-0060**
R.K. Cohn et al. (MI S U) "The Accuracy of Remapping Irregularly Spaced Velocity Data onto a Regular
Grid and the Computation of Vorticity"

(Statement A)

The Accuracy of Remapping Irregularly Spaced Velocity Data onto a Regular Grid and the Computation of Vorticity

R.K. Cohn and M.M. Koochesfabani

Department of Mechanical Engineering, Michigan State University, East Lansing, MI

The velocity data obtained from Molecular Tagging Velocimetry (MTV) are typically located on an irregularly spaced measurement grid. In this method of velocimetry, the flowing medium is premixed with a molecular complex that can be turned into a long life-time tracer upon excitation by photons. The velocity vector is determined from the displacement of small regions "tagged" by a pulsed laser which are imaged at two successive times within the lifetime of the tracer. This technique may be viewed as the *molecular* counterpart of PIV. To take advantage of standard data processing techniques, the MTV data need to be remapped onto a regular grid with a uniform spacing. In this work we examine the accuracy and noise issues related to the use of various low order polynomial least-square fits for remapping and the subsequent computation of vorticity from these data. The information obtained has relevance to PIV data processing as well. As noted by Spedding and Rignot (1993), the best estimate of the location of the velocity vector acquired through the use of tracer techniques, such as PIV, is at the midpoint of the displacement vector. Thus, unless special care is taken, PIV data are also initially obtained on an irregular grid.

In the past, various methods have been used for remapping randomly spaced velocity data onto a regular grid. Among them are an inverse distance approach and a "global basis function" examined by Spedding and Rignot (1993). In this study, we consider the use of 2nd, 3rd, or 4th order polynomial to remap the velocity field by performing a local least-squares fit of the irregularly spaced data within region of radius R . This choice was selected based on the work of Agui and Jimenez (1987), who report that low order polynomial fits and "kriging" techniques produce the most accurate representation of the actual velocity field. However, no quantitative information on the performance of these methods is presented. Four approaches are assessed here for computing the out-of-plane vorticity field from the in-plane velocity measurements: direct differentiation of the polynomial fits used in the remapping process, 1st and 2nd order finite difference techniques (2nd and 4th order accurate, respectively) and an 8-point circulation method on the regular data. It should be noted that the 8-point circulation method is identical to the 1st order finite difference method after an appropriate choice of smoothing.

Several authors have examined the accuracy of the various means to compute vorticity from regularly spaced data. Spedding and Rignot (1993) used a 1st order finite difference technique for the inverse distance method or directly differentiating the global basis function. Results indicated that the global basis function produced generally superior results, however, results were found to be highly dependent upon the ratio, of a characteristic length scale, of the flow, L , to the mean spacing between measurements, δ . Abrahamson and Lonnes (1995) found that the circulation method resulted in slightly more accurate vorticity results than using a least-squares fit to a model velocity field. Luff *et al.* (1999) compared the 1st and 2nd order finite difference methods and an 8-point circulation method in the calculation of vorticity in the presence of both noise and missing data points. In terms of only the computed vorticity RMS, the 1st order finite difference technique produced the best results.

One short-coming of the above mentioned studies is that only the random component of the error field is examined. Fouras and Soria (1998) found that the error in the vorticity field could be

better represented if it is divided into two portions: a mean bias error due to spatial filtering, and a random error resulting from the propagation of error in the velocity measurements into the calculation of vorticity. In some cases, the mean bias error can be significantly larger than the random error. The Fouras and Soria study found that differentiating a 2nd order polynomial least-squares fit to the velocity data produced results superior to the 1st order finite difference approach. However, the results based on differentiating the fit were sensitive to the number of points used in the fit. This work was based entirely on regularly sampled velocity data; issues connected to remapping an irregular data set were not considered.

The aforementioned investigations suggest different optimum methods for vorticity computation depending on the criterion used to assess the error. In our work we directly compare several of the different vorticity calculation methods which were determined in the previous studies to produce the best results. In addition, we include the effect of remapping of the velocity field on the accuracy of vorticity estimation. The differentiation of the polynomial fit, used in remapping, as a means of estimating the vorticity is also considered. A simulation of an Oseen vortex, utilized by the previous studies, is also employed here as the basis for comparison. The effect of uncertainty in the velocity measurements is simulated by adding a random amount of noise to each velocity component.

Our simulations show that the accuracy of the remapping process depends on both L/δ and the normalized size of the region used in the least-squares fit, R/δ . The effect of increasing the value of R/δ on the velocity and vorticity fields is to decrease the random error, but increase the mean bias error. Generally, the decrease in random error is smaller than the increase in the bias error. All of the different polynomial orders tested produced accurate results in the remapping of the velocity field for suitable choice of L/δ and R/δ . For example, with $L/\delta > 4.5$ both the velocity mean bias error and random error are less than 1% of the peak velocity.

Results show that the most accurate vorticity results are achieved by either directly differentiating the 3rd order polynomial fit to the original irregular data or by the 2nd order finite difference technique. Note that this conclusion is different from previous studies because they either did not consider the 2nd order finite difference approach, or the performance was based only on the random error. For $L/\delta > 4.5$, we find the mean bias error and random error in vorticity can be less than 3% and 2%, respectively, of the peak vorticity. A decrease in L/δ causes a large increase in the vorticity bias error; error values higher than 18% of the peak vorticity are found for $L/\delta = 2.5$.

References:

- Abrahamson, S. and Lonnes, S. [1995] "Uncertainty in calculating vorticity from 2D velocity fields using circulation and least squares approaches," *Exp. in Fluids*, **20**, pp. 10-20.
- Agui, J. and Jimenez, J. [1987] "On the performance of particle tracking," *J. Fluid Mechanics*, **186**, pp. 447-468.
- Fouras, A. And Soria, J. [1998] "Accuracy of out-of-plane vorticity measurements from in-plane velocity field data," *Exp. in Fluids*, **25**(5/6), pp. 409-430.
- Luff, J. D., Drouillard, T., Rompage, A. M., Linne, M. A., and Hertberg, J. R. [1999] "Experimental uncertainties associated with particle image velocimetry (PIV) based vorticity algorithms," *Exp. in Fluids*, **26**, pp. 36-54.
- Spedding, G. R. and Rignot, E. J. M. [1993] "Performance analysis and application of grid interpolation techniques for fluid flows," *Exp. in Fluids*, **15**, pp. 417-430.